


# EL DISPLAY PANEL, ITS DRIVING METHOD, AND EL DISPLAY APPARATUS

Patent Number: EP1424674  
 Publication date: 2004-06-02  
 Inventor(s): TAKAHARA HIROSHI [JP]; TSUGE HITOSHI [JP]  
 Applicant(s): MATSUSHITA ELECTRIC IND CO LTD [JP]  
 Requested Patent: WO03023750  
 Application Number: EP20020798040 20020906  
 Priority Number (s): WO2002JP09111 20020906; JP20010271311 20010907; JP20010291598 20010925; JP20010347014 20011113; JP20020136117 20020510  
 IPC Classification: G09G3/20; G09G3/30; G09G3/36  
 EC Classification: G09G3/32  
 Equivalents: CN1552050, US2005041002  
 Cited Documents:

## Abstract

An EL display apparatus according to the present invention includes EL device (15) adapted to emit light at a luminance corresponding to a current fed thereto. A source driver (14) outputs a current higher than a current corresponding to an image signal to the EL device (15) through a source signal line (18). This operation charges/discharges a parasitic capacitance present in the source signal line (18). A transistor (11d) formed between the EL device (15) and the source driver (14) operates so that the EL device (15) is fed with the current for only a part of a one-frame period. As a result, the EL device (15) emits light for only the part of the period. 

Data supplied from the esp@cenet database - I2

## Description

### Technical Field

[0001] The present invention relates to an EL display apparatus employing an organic or inorganic electroluminescence (EL) device and, more particularly, to an EL display apparatus capable of feeding an EL device with a desired current, a method of driving the same, and an electronic apparatus provided with such an EL display apparatus.

### Background Art

[0002] In general, an active-matrix display apparatus has a multiplicity of pixels arranged in matrix and displays an image by controlling the intensity of light pixel by pixel in accordance with image signals given. When, for example, liquid crystal is used as an electro-optic substance, the transmittance of each pixel varies in accordance with the voltage applied to the pixel. The basic operation of an active-matrix image display apparatus employing an organic electroluminescence (EL) material as an electro-optic converting substance is the same as in the case where liquid crystal is used.